

ViewSonic® Projectors



ViewSonic Projectors

Award-winning. Innovative. Dependable. ViewSonic brings you the most complete line of performance LCD and DLP® projectors from road-ready portables to models designed for large venues and entertainment. When you're navigating through a forest of projector options, let the visual experts at ViewSonic guide you.

Unmatched
Support

ViewSonic has the **best product warranty** and **service support** in the business!

**3 Year**

Parts and labor limited warranty

1 Year

Free Express Exchange® service

1 Year

Limited lamp warranty

	Ultra Portable			Wide Format	
	PJD2121	PJ260D	PJL3211	PJ359w	PJD6531w
Native Resolution	SVGA 800x600	XGA 1024x768	XGA 1024x768	WXGA 1280x800	WXGA 1280x800
Technology	DLP®	DLP®	3-panel LCD	3-panel LCD	DLP®
Brightness Lumens (max)	400	2,000	2,500	2,000	3,000
Contrast Ratio (max)	1800:1	2000:1	500:1	500:1	3200:1
Display Size (in.)	35–150	40–300	30–300	30–300	27–300
Aspect Ratio	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native), 16:9	16:10 (native), 4:3	16:10 (native), 4:3
Minimum Projection Throw Distance (in.)	28	63	31	35	27
Throw Ratio	1.0:1	1.9–2.25:1	1.3–1.5:1	1.5–1.8:1	1.7:1–2.1:1
Digital Keystone Correction	Yes	Yes	Yes, auto vert	Yes	Yes
Zoom/Focus Control	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Eco or Whisper-mode	No	Yes, eco-mode	Yes, eco-mode	Yes, eco-mode	Yes, eco-mode
Noise Level (dB) Normal/Eco or Whisper-mode	31	38/32	41/34	44/37	34/29
Lamp Life** (hrs.) Normal/Eco or Whisper-mode	2,000/3,000	2,000/3,000	2,000/3,000	2,000/3,000	4,000/6,000
Altitude (ft.)	0–10,000	0–10,000	0–10,000	0–10,000	0–6,000
Lamp Type (watts)	50	200	190	190	230
Net Weight (lb.)	2.2	2.9	4.1	3.9	5.9
Integrated Speakers	No	1x1-watt	1x1-watt	1x1-watt	2x5-watt
Mac® Compatible*	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/No	Yes/No	Yes/No	Yes/Yes	Yes/Yes
RGB Inputs/Outputs	1/–	1/–	2/–	2/–	2/1
Additional Inputs	RCA Jack	S-video, composite	S-video, component (DB-15), composite	S-video, component (DB-15), composite	HDMI, S-video, component (DB-15), composite, audio
HD Ready	Yes	Yes	Yes	Yes	Yes
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions W x H x D (in.)	8.1 x 4.7 x 2.6	8.6 x 2.7 x 6.7	10.8 x 2.3 x 8.1	10.8 x 2.3 x 8.1	11.0 x 4.5 x 8.6
Power Consumption - watts (typ)	90	260	310	310	305
Includes Soft Case	Yes	Yes	Yes	Yes	Yes
Limited Lamp Warranty	1-year	1-year	1-year	1-year	1-year
First-Year Express Exchange®	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3-year	3-year	3-year	3-year	3-year

BEAM SCAN

Communications Pvt. Ltd.

The people behind your Presentations...

Address: #33/3, 8th Main Road,
12th Cross, Malleshwaram, Bangalore - 560 003, Karnataka, India
Phone No.: +91 80 2346 3159 Telefax: +91 80 2346 2279
E-Mail: ho@beamscan.in, beamscan@rediffmail.com
Website: www.beamscan.in

ViewSonic®
See the difference® 



WPG-350 Wireless Presentation Gateway

Set your presentations free. Wirelessly connect your notebook or desktop PC to any projector. Take your presentations anywhere with 802.11b/g/n connectivity and easily experience dynamic, interactive meetings without swapping cables. Supports any projector, LCD or LCD TV with a VGA connector. Visit ViewSonic.com for full details and specifications.

Unmatched Support

ViewSonic has the **best product warranty** and **service support** in the business!



3 Year

Parts and labor limited warranty

1 Year

Free Express Exchange® service

1 Year

Limited lamp warranty

	Entry SVGA		Short Throw		Entry XGA	
	PJD5111	PJD5112	PJD5351	PJD6381	PJD6211	PJL7211
Native Resolution	SVGA 800x600	SVGA 800x600	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768
Technology	DLP®	DLP®	DLP®	DLP®	DLP®	3-panel LCD
Brightness Lumens (max)	2,500	2,600	2,500	2,500	2,500	2,200
Contrast Ratio (max)	2000:1	2800:1	2000:1	2400:1	2000:1	400:1
Display Size (in.)	35–155	27–300	35–180	30–300	30 – 300	30 – 300
Aspect Ratio	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native)
Minimum Projection Throw Distance (in.)	59	47	29	16	47	31
Throw Ratio	1.86-2.04:1	1.6–1.9:1	0.9:1	0.68:1	1.6–1.9:1	1.4 – 1.7:1
Digital Keystone Correction	Yes	Yes	Yes	Yes	Yes	Yes
Zoom/Focus Control	Manual/Manual	Manual/Manual	Digital/Manual	Manual/Auto	Manual/Manual	Manual/Manual
Eco or Whisper-mode	Yes, eco-mode	Yes, eco-mode	Yes, eco-mode	Yes, eco-mode	Yes, eco-mode	Yes, eco-mode
Noise Level (dB) Normal/Eco or Whisper-mode	30/27	30/26	30/27	30/29	31/29	37/30
Lamp Life** (hrs.) Normal/Eco or Whisper-mode	3,000/4,000	3,000/5,000	3,000/4,000	4,000/6,000	4,000/5,000	3,000/6,000
Altitude (ft.)	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000
Lamp Type (watts)	189	180	189	230	180	190
Net Weight (lb.)	5.1	5.7	5.5	5.9	5.9	7.3
Integrated Speakers	1x5-watt	1x2-watt	1x5-watt	2x5-watt	1x2-watt	No
Mac® Compatible*	Yes	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/No	Yes/No	Yes/No	Yes/Yes	Yes/Yes	Yes/No
RGB Inputs/Outputs	2/1	2/1	2/1	2/1	2/1	1/–
Additional Inputs	S-video, component (DB-15), composite	S-video, component (DB-15), composite, audio	S-video, component (DB-15), composite	S-video, component (DB-15), composite	S-video, component (DB-15), composite	S-video, component (DB-15), composite
HD Ready	Yes	Yes	Yes	Yes	Yes	Yes
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions- W x H x D (in.)	10.4 x 3.8 x 8.9	11.0 x 4.5 x 8.6	10.4 x 3.8 x 8.9	11 x 4.5 x 8.6	11 x 4.5 x 8.6	12.5 x 3.9 x 11.3
Power Consumption - watts (typ)	242	235	242	305	235	250
Includes Soft Case	No	No	Yes	Yes	No	No
Limited Lamp Warranty	1-year	1-year	1-year	1-year	1-year	1-year
First-Year Express Exchange®	FREE	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3-year	3-year	3-year	3-year	3-year	3-year



Address: #33/3, 8th Main Road,
12th Cross, Malleshwaram, Bangalore - 560 003, Karnataka, India
Phone No.: +91 80 2346 3159 Telefax: +91 80 2346 2279
E-Mail: ho@beamscan.in, beamscan@rediffmail.com
Website: www.beamscan.in



	Business & Education			Installation / Large Venue	
	PJD6221	PJD6241	PJD6251	PJL9371	PJ1173
Native Resolution	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768
Technology	DLP®	DLP®	DLP®	3-panel LCD	3-panel LCD
Brightness Lumens (max)	2,700	3,200	3,700	4,000	5,000
Contrast Ratio (max)	2800:1	3200:1	2800:1	2000:1	1000:1
Display Size (in.)	30 – 300	27 – 300	27–300	30–300	30–350
Aspect Ratio	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native), 16:9
Minimum Projection Throw Distance (in.)	47	47	32.8	35	35
Throw Ratio	1.6 – 1.9:1	1.9 – 2.1:1	1.8:1–2.1:1	1.5–1.8:1	1.5–1.8:1
Digital Keystone Correction	Yes	Yes	Yes	Yes, auto vert	Yes, auto vert
Zoom/Focus Control	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Eco or Whisper-mode	Yes	Yes, eco-mode	Yes, eco-mode	Yes, whisper-mode	Yes, whisper-mode
Noise Level (dB) Normal/Eco or Whisper-mode	31/29	34/32	37/35	36/29	39/33
Lamp Life** (hrs.) Normal/Eco or Whisper-mode	3,500/5,000	4,000/6,000	4,000/5,000	3,000/5,000	2,000/3,000
Altitude (ft.)	0–10,000	0–10,000	0–10,000	0-12,000	0–12,000
Lamp Type (watts)	180	230	280	260	275
Net Weight (lb.)	5.8	5.9	6.1	9.5	15.6
Integrated Speakers	1x2-watt	2x5-watt	2x5-watt	2x8-watt	4x4-watt
Mac® Compatible*	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes
RGB Inputs/Outputs	2/1	2/1	2/1	2/1	3/1
Additional Inputs	S-video, component (DB-15) composite	S-video, component (DB-15), composite, audio	S-video, component, composite	S-video, component, composite	HDMI, S-video,component, composite
HD Ready	Yes	Yes	Yes	Yes	Yes
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions- W x H x D (in.)	11 x 4.5 x 8.6	11.0 x 4.5 x 8.6	11x 4.5 x 8.6	9.5 x 3.9 x 12.5	16.5 x 5.5 x 12.6
Power Consumption - watts (typ)	235	305	350	390	460
Includes Soft Case	No	Yes	Yes	No	No
Limited Lamp Warranty	1-year	1-year	1-year	1-year	1-year
First-Year Express Exchange®	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3-year	3-year	3-Year	3-Year	3-Year



Replacement Lamps
ViewSonic offers longlife, user-installable replacement lamps for all our projectors.

PROJECTOR SPARE LAMPS

MODEL	DESCRIPTION
RLC-018	Replacement lamp for PJ506D, PJ556D
RLC-021	Replacement lamp for PJ1158
RLC-023	Replacement lamp for PJ558D
RLC-025	Replacement lamp for PJ258D
RLC-026	Replacement lamp for PJ588D
RLC-027	Replacement lamp for PJ358
RLC-030	Replacement lamp for PJ503D
RLC-031	Replacement lamp for PJ759
RLC-033	Replacement lamp for PJ260D
RLC-034	Replacement lamp for PJ551D, PJ557D, PJD6220
RLC-036	Replacement lamp for PJ559D, PJD6230
RLC-037	Replacement lamp for PJ560D, PJD6240
RLC-038	Replacement lamp for PJ1173
RLC-039	Replacement lamp for PJ359w, PJL3211
RLC-041	Replacement lamp for PJD5111
RLC-047	Replacement lamp for PJD5351
RLC-049	Replacement lamp for PJD6381, PJD6241, PJD6531w
RLC-050	Replacement lamp for PJD6211, PJD6221, PJD5112
RLC-051	Replacement lamp for PJD6251
RLC-052	Replacement lamp for PJD2121
RLC-053	Replacement lamp for PJL9371
RLC-054	Replacement lamp for PJL7211

PROJECTOR CASES AND MOUNTS

MODEL	DESCRIPTION
WMK-005	Universal ceiling mount (not compatible with 2 lb. projectors)
WMK-027	Short throw wall mount (compatible with PJD5351, PJD6381)

See ViewSonic.com for a full list of projector accessories.



Address: #33/3, 8th Main Road,
12th Cross, Malleshwaram, Bangalore - 560 003, Karnataka, India
Phone No.: +91 80 2346 3159 Telefax: +91 80 2346 2279
E-Mail: ho@beamscan.in, beamscan@rediffmail.com
Website: www.beamscan.in

